

Splitter Module CAN-RSPLIT-10X

Overview

Ensures professional splitting and branching of fiber based on bandwidth requirements with mechanical splitters and provides professional cable management.

Highlights

- Confirms 19" or ETSI installations
- 1U (enables splitting up to 32 ports)
- Fiber trays with integrated, high-quality splitters and pre-terminated fiber ends
- Quick-stud system ensures easy closing/opening of the unit
- Easy access with telescopic rail pull-out system
- Special bend radii for protecting the incoming and outgoing fiber from bending
- 100% Compatible to Bellcore GR-326 standards
- 1:2, 1:4, 2:4, 1:8, 2:8, 1:16, 2:16, 1:32, 2:32 splitters of all connector types can be embedded inside

Technical Details

Dimensions	443 mm (W) x 272 mm (D) x 44 mm (H)
Material	Mild Steel, 1,5 mm
Color	Powder-Coated Median Grey NCS 2502B
Weight	4,5 kg (1U)

Applications

In ODF's and high density outdoor fiber applications on Carrier & Transmission level, FTTX applications, Utility Companies.

Splitter Type	Splitter Quantity	Product code
1X2 SC/APC	11	CAN-RSPLIT-101
2X4 SC/APC	1	CAN-RSPLIT-102
2X8 SC/APC	1	CAN-RSPLIT-103
2X16 SC/APC	1	CAN-RSPLIT-104
2X32 SC/APC	1	CAN-RSPLIT-105

